



Product Service

Attestation of Conformity

No. E8A 115067 0040 Rev. 00

Holder of Certificate: **Xiamen Kehua Digital Energy Tech Co., Ltd.**

Room 208-38, Hengye Building
No. 100 Xiangxing Road
Torch High-tech Zone
(Xiang'an) Industrial Zone
361115 Xiamen
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Converter
(Energy Storage Inverter)**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64772223111101

Date, 2022-09-30

(Peter Jia)

Page 1 of 3

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. E8A 115067 0040 Rev. 00

Model(s): iStoragE3 5K, iStoragE3 6K, iStoragE3 8K,
iStoragE3 10K, iStoragE3 12K

Trade name: KEHUA



Description of Object:

Model	iStoragE3 5K	iStoragE3 6K	iStoragE3 8K	iStoragE3 10K	iStoragE3 12K
PV terminal parameters					
Vmax. PV	1000 Vd.c.	1000 Vd.c.	1000 Vd.c.	1000 Vd.c.	1000 Vd.c.
MPPT Voltage Range	150 Vd.c.~ 900 Vd.c.	150 Vd.c.~ 900 Vd.c.	150 Vd.c.~ 900 Vd.c.	150 Vd.c.~ 900 Vd.c.	150 Vd.c.~ 900 Vd.c.
MPPT Voltage Range (full load)	450 Vd.c.~ 750 Vd.c.	450 Vd.c.~ 750 Vd.c.	450 Vd.c.~ 750 Vd.c.	450 Vd.c.~ 750 Vd.c.	450 Vd.c.~ 750 Vd.c.
Max. continuous PV input current	16 Ad.c./ 16 Ad.c.	16 Ad.c./ 16 Ad.c.	27 Ad.c./ 16 Ad.c.	27 Ad.c./ 16 Ad.c.	27 Ad.c./ 16 Ad.c.
Isc PV	20 Ad.c./ 20 Ad.c.	20 Ad.c./ 20 Ad.c.	34 Ad.c./ 20 Ad.c.	34 Ad.c./ 20 Ad.c.	34 Ad.c./ 20 Ad.c.
Max. continuous PV input power	23000 W	23000 W	29000 W	29000 W	29000 W
Battery terminal parameter					
Battery type	LFP	LFP	LFP	LFP	LFP
Voltage range	650 Vd.c.~ 900 Vd.c.	650 Vd.c.~ 900 Vd.c.	650 Vd.c.~ 900 Vd.c.	650 Vd.c.~ 900 Vd.c.	650 Vd.c.~ 900 Vd.c.
Rated voltage	720 Vd.c.	720 Vd.c.	720 Vd.c.	720 Vd.c.	720 Vd.c.
Maximum charge/discharge current	24.6 Ad.c.*/ 8.5 Ad.c.	24.6 Ad.c.*/ 10.2Ad.c.	24.6Ad.c.*/ 13.5Ad.c.	24.6Ad.c.*/ 16.9Ad.c.	24.6Ad.c.*/ 18.5Ad.c.
Maximum charge current from grid to battery	8.5 Ad.c.	10.2 Ad.c.	13.5 Ad.c.	16.9 Ad.c.	18.5 Ad.c.
Maximum charge/discharge power	16000 W*/ 5500 W	16000 W*/ 6600 W	16000 W*/ 8800 W	16000 W*/ 11000 W	16000 W*/ 12000W
Maximum charge power from grid to battery	5500 W	6600 W	8800 W	11000 W	12000 W
Grid terminal parameter					
Rated voltage	230/400 Va.c., 3W+N+PE				

Page 2 of 3

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. E8A 115067 0040 Rev. 00

Rated frequency	50 Hz				
Rated current output to Grid	7.2 Aa.c.	8.7 Aa.c.	11.6 Aa.c.	14.5 Aa.c.	17.4 Aa.c.
Maximum continuous current output to Grid	7.9 Aa.c.	9.6 Aa.c.	12.8 Aa.c.	16.0 Aa.c.	17.4 Aa.c.
Rated active power output to Grid	5000 W	6000 W	8000 W	10000 W	12000 W
Maximum apparent power output to Grid	5500 VA	6600 VA	8800 VA	11000 VA	12000 VA
Maximum continuous current from Grid	14.4 Aa.c.	17.4 Aa.c.	23.2 Aa.c.	26.0 Aa.c.	26.0 Aa.c.
Maximum apparent power from Grid	10000 VA	12000 VA	16000 VA	18000 VA	18000 VA
Power factor (Cos phi), adjustable	0.8 leading to 0.8 lagging				
Back up load terminal parameter					
Rated voltage	230/400 Va.c., 3W+N+PE				
Rated frequency	50 Hz				
Rated output Current	7.2 Aa.c.	8.7 Aa.c.	11.6 Aa.c.	14.5 Aa.c.	17.4 Aa.c.
Maximum continuous output current	7.9 Aa.c.	9.6 Aa.c.	12.7 Aa.c.	15.9 Aa.c.	17.4 Aa.c.
Maximum continuous output power	5500 VA	6600 VA	8800 VA	11000 VA	12000 VA
Power factor (Cos phi), adjustable	0.8 leading to 0.8 lagging				
General					
Operating temperature range	-20 °C ~ 50 °C (Auto derating above 35 °C)				
Protection class	I				
Ingress protection	IP65				
Operating altitude range	2000m				
Remark: All aspects of the essential requirements were assessed. The certificate is only valid if no transmitting radio equipment is included in the device (WiFi, 4G, RFID).					

**Tested
according to:**EN IEC 61000-6-1:2019
EN IEC 61000-6-2:2019
EN IEC 61000-6-3:2021
EN IEC 61000-6-4:2019

Page 3 of 3

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.